



LOCTITE® SI 5904

February 2025

Product description

LOCTITE® SI 5904 provides the following product characteristics:

Technology	Silicone
Chemical type	Oxime silicone
Appearance (uncured)	Black paste
Thixotropic	Reduced migration of liquid product after application to substrate
Components	One component - requires no mixing
Cure	Room temperature vulcanizing (RTV)
Application	Sealing
Specific benefits	Excellent resistance to automotive engine oils

LOCTITE® SI 5904 is a non-slumping, non-corrosive, low odour, low volatile, single component, room temperature vulcanising (RTV) silicone adhesive / sealant. Typical applications include stamped or casting flange parts (timing covers, bedplates, oil seal covers and oil sumps) where good oil resistance and the ability to withstand high joint-movement is required. It withstands on line, low pressure tests carried out before product begins to cure.

Typical properties of uncured material

Specific gravity @ 20°C	1.27
Extrusion rate, gm/min: (3mm nozzle, 6 bar, 25°C)	50
Flash point - see SDS	

Typical curing performance

Surface cure

Tack free time, minutes:	8
Cured @ 23±2°C, 60±5%RH.	

Cure through volume

Cure depth, mm/day:	2.6
Cured @ 23±2°C, 60±5%RH.	

Typical properties of cured material

Cured for 7 days @23±2°C, 60±5%RH

Elongation, at break, ISO 527-3, %	440
Tensile strength, ISO 527-3, N/mm ²	2.2
Shore hardness, ISO 868, Durometer A	40

Typical performance of cured material

Cured for 7 days @23±2°C, 60±5%RH

Adhesive properties

Lap shear strength, ISO 4587, N/mm ² Aluminium / Aluminium 1.0 mm gap	1.7
Lap shear strength, ISO 4587, N/mm ² Aluminium / Steel 1.0 mm gap	1.6
Lap shear strength, ISO 4587, N/mm ² Steel / Steel 1.0 mm gap	1.7
All substrates are grit-blasted Aluminium: Aluminium 2024 T3	

Typical environmental resistance

Cured for 7 days @ 23±2°C, 60±5% RH

Lap shear strength, ISO 4587: Grit blasted Aluminium 2024 T3 / Aluminium 2024 T3 @1mm bond gap
Elongation at break, ISO 527-3
Shore hardness, ISO 868, Durometer A

Typical fluid immersion properties

Tested 23°C

% Initial Value retained at				
Motor oil 5W20 @150°C				
	100h	300h	500h	1000h
Hardness Shore A	68	70	62	47
Elongation	86	92	91	100
Tensile strength	132	130	129	114
Lap shear strength	132	134	115	96

General information

This product is not recommended for use in pure oxygen and/or oxygen rich systems and should not be selected as a sealant for chlorine or other strong oxidizing materials.

For safe handling information on this product, consult the Safety Data Sheet (SDS).

Directions for use

1. For best performance bond surfaces should be clean and free from grease.
2. This product is moisture cure. Exposure to environmental moisture should be kept to a minimum during storage and handling.
3. Moisture curing begins immediately after the product is exposed to the atmosphere, therefore parts to be assembled should be mated within a few minutes after the product is dispensed.
4. The bond should be allowed to cure (e.g. seven days), before subjecting to heavy service loads.
5. Excess material can be easily wiped away with non-polar solvents.



Storage

Store product in the unopened container in a dry location. Storage information may be indicated on the product container labeling.

Optimal storage: 8°C to 21°C. Storage below 8°C or greater than 21°C can adversely affect product properties.

Material removed from containers may be contaminated during use. Do not return product to the original container. Henkel Corporation cannot assume responsibility for product which has been contaminated or stored under conditions other than those previously indicated. If additional information is required, please contact your local Henkel representative.

Data Ranges

The data contained herein may be reported as a typical value and/or range. Values are based on actual test data and are verified on a periodic basis.

Conversions

$(^{\circ}\text{C} \times 1.8) + 32 = ^{\circ}\text{F}$

$\text{kV/mm} \times 25.4 = \text{V/mil}$

$\text{mm} / 25.4 = \text{inches}$

$\mu\text{m} / 25.4 = \text{mil}$

$\text{N} \times 0.225 = \text{lb}$

$\text{N/mm} \times 5.71 = \text{lb/in}$

$\text{N/mm}^2 \times 145 = \text{psi}$

$\text{MPa} \times 145 = \text{psi}$

$\text{N}\cdot\text{m} \times 8.851 = \text{lb}\cdot\text{in}$

$\text{N}\cdot\text{m} \times 0.738 = \text{lb}\cdot\text{ft}$

$\text{N}\cdot\text{mm} \times 0.142 = \text{oz}\cdot\text{in}$

$\text{MPa}\cdot\text{s} = \text{cP}$

Disclaimer

The information provided in this Technical data sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product. Any liability in respect of the information in the Technical data sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product. Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Corporation, or Henkel Canada Corporation, the following disclaimer is applicable:

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

Trademark usage

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

Reference 1